

Numerical Optimization of Half-Tunnel Concrete Formwork System using FEA



Avinash S, Ramesh Kannan M

Abstract: *This research seeks to develop a comprehensive framework for the design of Half-Tunnel Concrete Formwork System (HTCFS). HTCFS are highly efficient systems that are used for the construction of modular RCC structural systems. Additionally, HTCFS are significant in terms of higher reuse in constructing modular units. Despite these advantages, the actual design procedure adapted for HTCFS was not well elucidated so far, many companies adapt their own design methodology and hence it is highly important to develop a simplified straight forward design methodology incorporating all comprehensive associated factors. Initially, the detail introspective assessment of various types of HTCFS are perceived. Then using this information, a 3D Solid model is developed, and eventually, the 3D model gets converted into 3D solid CAE model using sophisticated Finite Element package for the Finite Element Analysis (FEA). This procedure is repeated for different combinations of components that construed effective systematized HTCFS. From the FEA the optimal structural components required for the structural integrity of HTCFS are established.*

Keywords: *Half-Tunnel Concrete Formwork System, Design intend, Finite Element Analysis, Numerical Optimization, Modular Construction.*

I. INTRODUCTION

Half-Tunnel Concrete Formwork Systems (HTCFS) are special types of concrete formwork systems that are used for the construction of repetitive modular RCC structural systems. Generally, HTCFS are used in the construction of modular RCC residential high-rise buildings that are symmetrical in terms of construction sequence, or in other words, repeatable construction patterns. There are many advantages of HTCFS, such as maximum formwork reuse, faster construction process, and lesser wastages of concrete and so on. The design of HTCFS is not well-established, as many construction companies that uses HTCFS develop their

own design methodology based on their experience and knowledge derived from their respective codal provisions and standards, and from the knowledge obtained from the constructability review. Thus, a simplified and straight forward design methodology for the construction of HTCFS is necessitated.

II. REVIEW OF LITERATURE

HTCFS comprises of various parts such as corrugated metal sheeting, buildup section steel whaler beams, buildup steel section struts, and plumbing struts with rocker and so on. Moreover, the dimensions of these components may vary depending upon the dimension of the casting specimen, intensity of the pressure, environmental condition. The optimum dimensions of these components are arrived based on trial and error. Different companies have got different design intends. Neru Formwork Systems (2014) developed a railed tunnel formwork system to construct a modular RCC structural systems based on international standards with special structural components such as NPU120 steel profile, adjustable fixing props and so on. Outinord Formworks (2015) proposed a special type of mechanized Tunnel formwork system for the construction of multi-storey residential structure known as Modular Tunnel Formwork TMPH based on standard tunnel form. Dema Formwork Systems (2014) developed three intriguing types of tunnel formwork systems known as Dema Classic Tunnel Form Systems (DCTFS), Dema Classic Plus Tunnel Form Systems (DCTFS+), and Dema Advanced Tunnel Form Systems. These tunnel formwork systems are used for the construction of modular RCC residential construction projects as well as heavy infrastructure projects. Mesa formwork (2018) has introduced three types of advanced formwork systems such as Classic Tunnel Formwork (TRTF), Modified Tunnel Formwork (MKTF), and Modular Tunnel Formwork (ERTF). The remarkable features of ERTF is that it incorporates adjustable telescopic push-pull props, elevated bottom tie-rod level for higher kicker concrete, telescopic extension tunnel legs for non-typical floors, and stripping platform extension leg for non-typical floors.

The following are the some of the advantages of HTCFS:

- Maximum reuse or repetition
- Faster rate of construction
- Efficient cycle time
- Fair-faced concrete finishes
- Durable and sustainable concrete construction (Lean strategy in concrete construction)

Manuscript received on March 15, 2020.

Revised Manuscript received on March 24, 2020.

Manuscript published on March 30, 2020.

* Correspondence Author

Mr. Avinash S*, Graduate Student, Division of Structural and geo-technical Engineering, School of Civil engineering, Vellore Institute of Technology Chennai, Tamil Nadu, India. Email: avinash.s2018@vitstudent.ac.in

Dr. Ramesh Kannan M*, Assistant Professor Senior, Division of Structural and geo-technical Engineering, School of Civil engineering, Vellore Institute of Technology Chennai, Tamil Nadu, India. Email: rameshkannan.m@vit.ac.in

© The Authors. Published by Blue Eyes Intelligence Engineering and Sciences Publication (BEIESP). This is an [open access](https://creativecommons.org/licenses/by-nc-nd/4.0/) article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>)

- Quality of constructed facilities

Kanoglu (2020) has portrayed the advantages and disadvantages of tunnel formwork systems. Kanoglu also emphasized the limitation of the design and construction phases associated with the construction of the tunnel formwork systems.

III. PRELIMINARY ANALYSIS

The detailed analogy of various design intents are described in this section. Initially, a conceptual framework of HTCFS is considered for static analysis as shown in Fig. 1. The result obtained from the static analysis is tabulated in Table 1.




Fig 1. Conceptual skeletal framework for static analysis

Table 1. Result of the Static Analysis

S.No	Member /Support	Force	Description
1.	AB or BA	67.39 KN	Tension
2.	BC or CB	-110.69 KN	Compression
3.	CD or Dc	32.30 KN	Tension
4.	AD or DA	-53.82 KN	Compression
5.	AC or CA	184.58 KN	Tension
6.	Vertical reaction at support C	-96.81 KN	Downward
7.	Horizontal reaction at support C	35 KN	Rightward
8.	Vertical reaction at support D	30.07 KN	Upward

The results obtained from the skeletal framework are satisfactory and showing appreciable constructability characteristics to be incorporated for real-time construction process. The constructability consideration for formwork systems are paramount important (Kannan and Knight, 2012; Kannan and Santhi, 2013, 2013a, 2018, 2019).

IV. 3D SOLID MODELLING

From the preliminary design considerations, the 3D solid model of HTCFSs are developed using one of the industry standard solid modelling software known as Dassault Systemes Solidworks. The components of HTCFS and its design intents are tabulated in Tables 2 and 3.

Table 2. Dimension of the HTCFS main components

Component	Dimension
Wall Board	2150 X 2450 (L X H) T= 4, 8, 12 mm
Curtain Board	2450 X 2800 (L X H) T= 4, 8, 12 mm
Spindle	L= 3920 mm Diameter= 50 mm
Bolts	1. M 14 X 80 mm 2. M 14 X 30 mm

Table 3. Dimension of the HTCFS auxillary components

S.No	Components of Half-Tunnel Formwork	Dimension
1	Top plate or slab plate	1.5*2.5m
2	Wall plate or side plate	3*2.5m
3	Fasteners	50*50mm
4	Props	60 mm dia, 5mm thickness
5	Wheel post	20*20 cm
6	Bolts	Head diameter 30mm, pitch 2mm
7	Thickness of top and side slab	5mm

Using the design parameters and intends from Tables 2 and 3, the 3D solid HTCFS of variable thickness such as 4 mm, 8 mm and 12 mm are developed. The 3D solid HTCFS with 8 mm thickness is shown in Fig. 2.




Fig 2. 3D solid HTCFS model with 8 mm thickness plates

A preliminary static analysis is performed in Dassault Systemes Solidworks for the three models, i.e., 3D solid HTCFS model with thicknesses 4 mm, 8 mm, and 12 mm. The 4 mm model and 12 mm model does not show appreciable result in terms of deformation, i.e., the 4 mm shows huge deformations (low-strength design) and on the otherside, 12 mm model shows no deformation (very conservative design) and hence a linear programming problem is carried out to determine the optimal thickness (Naidu and Kannan, 2015). From the LPP, the optimal thickness achieved is 7.82 mm, and hence 8 mm thickness is considered for practical consideration.

V. FEA OF HALF TUNNEL FORMWORK SYSTEM

From the optimization, the 3D solid HTCFS model with optimal thickness (i.e., 8 mm) is considered for Finite Element Analysis. Initially, a detailed meshed model from the optimal 3D solid HTCFS model is created in ANSYS as shown in Fig. 3. The design parameters are tabulated in Table 4.




Fig 3. 3D solid meshed HTCFS model (Preliminary mesh showing different mesh pattern for illustration only)

Table 4. Design parameters for the HTCFS

Parameters	Numbers
Bodies	38
Active bodies	38
Nodes	433274
Elements	222967

The types of mesh considered is triangular very fine or very condensed mesh pattern. Finer the mesh, the more accurate the result or consensus but the computation time will be higher. Using the selected meshed type, the FEA is performed in ANSYS. The results obtained from the FEA are illustrated in the Figs. 4-7.




Fig 4. Equivalent stress in the HTCFS model




Fig 5. Equivalent elastic strain in the HTCFS model




Fig 6. Total deformation in the HTCFS model

From Fig. 6, the total deformation is within the allowable limit and hence this model sustanciate the constructability conditions.




Fig 7. Safety factor for the HTCFS model.

VI. RESULTS AND DISCUSSIONS

Since the resulting 3D FEA models (Figs. 4-7) gives comprehensive and promising results in the statics analysis, it is thus expanded to dynamic analysis in ANSYS. The outcomes of the dynamic analysis are reported in Table 5.

Table 5. Result of dynamic analysis (frequency, time period, total deformation of modal analysis) for HTCFS

Mode	Frequency (Hz)	Time period (sec)	Total deformation (mm)
1	1.6626	0.6024	1.7114
2	3.8217	0.2617	2.8874
3	11.428	0.0874	4.7633
4	11.844	0.0844	3.6382
5	17.414	0.0574	2.959
6	21.264	0.0470	6.1804

VII. CONCLUSION

The FEA methodology adopted for the HTCFS in this research, provides a comprehensive analysis design strategy to the HTCFS, which would certainly enhance the designing of this special type of formwork system and also enrich the constructability consideration in the real-time construction site. Albeit the static analysis shows promising results, the dynamic analysis could not portray much on the significance of the structural behavior or structural integrity of the HTCFS, however a detailed study including the time effects of concrete, rheological or thixotropic behavior of concrete (Kumar and Kannan, 2015; Tamrakar and Kannan, 2015; Shanmughan and Kannan, 2016) in the 3D FEA can be carried to infer the dynamic response of the HTCFSs.

REFERENCES

1. Technical Committee, Tunnel Formwork, Technical/Product Manual, Neru Formwork System, Turkey, 2014.
2. Technical Committee, Tunnel Formwork, Technical/Product Manual, Dema Formwork System, Turkey, 2014.
3. Technical Committee, Tunnel Formwork, Technical/Product Manual, Mesa Formwork System, USA, 2018.
4. A. Kanoglu, Tunnel Formwork System, Lecture Notes, Faculty of Architecture, Istanbul Technical University. (Accessed on March, 2020)
5. M. R. Kannan and S. Knight. "Constructability – the paradigm shift in the construction engineering and management." In Proceedings of the International conference on emerging technological trends in advanced engineering research, Baseli Mathews II College of Engineering, Kollam, Kerala, India. 2012.
6. M. R. Kannan, M. H. Santhi, Constructability Assessment of Climbing Formwork Systems Using Building Information Modeling, Procedia Engineering, vol. 64, 2013, pp. 1129-1138.
7. M. R. Kannan, M. H. Santhi, Automated construction layout and simulation of concrete formwork systems using building information modeling. In Proceedings of the 4th International Conference of Euro Asia Civil Engineering Forum, National University of Singapore, Singapore, 2013a, vol. 64, pp. C7-C12.
8. S. Naidu, R. Kannan, Numerical Optimization of Shoring Towers for Slab Formwork Systems, International Journal For Trends In Engineering & Technology, vol. 5(1), pp. 114-120.
9. Kannan, M.R., Santhi, M.H. Automated constructability rating framework for concrete formwork systems using building information modeling. Asian J Civ Eng, 2018, vol. 19, pp. 387-413.
10. M. R. Kannan, Constructability Analysis of Concrete Formwork Systems, PhD Thesis, Vellore Institute of Technology, 2019.
11. N. Kumar and R. Kannan, Experimental Investigation of Lateral Pressure on Vertical Formwork Systems using Self Compacting Concrete, International Journal for Trends in Engineering & Technology, 2015, vol. 5, issue 2, pp. 54-58.
12. R. Tamrakar, R. Kannan, Response of Slab Form for Different Concrete Pressure, International Journal for Trends in Engineering & Technology, 2015, vol. 7, issue 1, pp. 54-58.
13. S. Shanmughan, and R. Kannan, Modelling of Formwork Pressure Using Self-Compacting Concrete by Numerical Methods for Attaining Environmental Sustainability. Key Engineering Materials 2016, vol. 692, pp. 119-28.

AUTHORS PROFILE



Mr. Avinash S was born in Vellore, Tamil Nadu, India. He received his B.Tech degree in Civil Engineering from Vellore Institute of Technology, Vellore, India in 2018 and M.Tech degree in Structural Engineering from Vellore Institute of Technology, Chennai, India. His area of research includes Structural Engineering.



Dr. Ramesh Kannan M was born in Madurai, Tamil Nadu, India. He received his B.E. degree in Civil Engineering from Hindustan College of Engineering, Affiliated to Anna University, Chennai, India in 2010 and M.E. degree in Construction Engineering and

Management from College of Engineering Guindy, Anna University, Chennai, India and PhD in Civil Engineering from Vellore Institute of Technology Chennai. Since 2012, he is in VIT Chennai, India, where he is currently working as Assistant Professor Sr in School of Civil Engineering. His area of research interests includes Building Information Modeling (BIM), constructability assessment, concrete formwork systems and structural optimization and concrete technology.